



# Check Seal™ 357P Non-Curing Sealant

**Check Seal™ 357P** is a non-curing sealant that contains a blend of non-asbestos fibers in synthetic oils. It works great on valve packing and wire wrap fugitive emission repairs, and is specifically designed for high temperature hydrocarbon service up to 750°F.

## Typical Characteristics

Applications	Glycols, hydrocarbons, water, steam, bfw and many solvents. Good general purpose, high temperature valve packing.
<b>Note: For chemicals, refer to compatibility chart</b>	
Temperature Range	-300°F to 750°F
Appearance	Black, fibrous
Injection Characteristics	900 psi - Flows well at higher pressures
Cure	Non-curing
Long Term Changes	None; permanent packing, may be added to
Storage	Keep in dry area

## Packaging Information

Item Number	Unit Size	Quantity
CS082316JBX	300J-12 "J" stick 1-3/8" x 8-1/2"	16 per box
CS0823001PL	3/4" x 4" plugs	10 per pouch

**DO NOT USE ON OXYGEN SERVICE.**  
*Special packaging sizing available upon request.*

# SOUTH COAST PRODUCTS

P.O. Box 450109 Houston, Texas 77245 [www.socousa.com](http://www.socousa.com)  
Tel: (713) 225-0048 (800) 535-5823 [custserv@socousa.com](mailto:custserv@socousa.com)

# Premium