



Check Seal™ 3B Non-Curing Sealant

Check Seal™ 3B semi-pliable rubber at temperatures up to 700°F, and is effective as a primary or secondary sealant. It has been successfully used as a secondary micro-void sealant after initial sealant becomes cracked and worm holed.

Typical Characteristics

Applications	Acids, steam, some solvents, fuels, glycols, mild alkalis, aliphatic hydrocarbons, hot oils, kerosene, steam, water, liquors. It also has been used successfully as a secondary micro-void filler after injecting a different sealant on the real problem leaks.
Note: For chemicals, refer to compatibility chart	
Temperature Range	-300°F to 700°F
Limitations	Should not be used at temps over 700°F (371°C)
Appearance	Yellow paste
Specific Gravity	0.9
Volume	191 cu. in – 1 gal pail
Volume	12.6 cu. in – J stick
Volume	1.1 cu. in – 3.5" plug
Injection Characteristics	500 psi, flows well with minimum hydraulic pressure
Cure	Cures at 350°F to 400°F, non-curing at lower temps
Long Term Changes	None
Storage	Keep at room temperature

Packaging Information

Item Number	Unit Size	Quantity
CS300211	1 gal pail, 5 lb	
CS300511	"J" stick 1-3/8" x 8-1/2"	16 per box
CS08265001PL	3/4" x 4 plugs	10 per box

DO NOT USE ON OXYGEN SERVICE.
Special packaging sizing available upon request.

SOUTH COAST PRODUCTS

P.O. Box 450109 Houston, Texas 77245 www.socousa.com
Tel: (713) 225-0048 (800) 535-5823 custserv@socousa.com

