



Check Seal™ 17 RTV Silicone Sealant

Check Seal™ 17 RTV is a one-component high temperature silicone sealant that cures to a pliable, low durometer solid. It is formulated for use with water and steam-based services.

Typical Characteristics

| | |
|--|---|
| Applications | Acids, glycols, hydrocarbons, refrigerants, water, steam, bfw and many solvents CAUTION: Some of the additives in the steam and bfw can kill the cure. |
| Note: For chemicals, refer to compatibility chart | |
| Temperature Range | -300°F to 600°F |
| Limitations | Should not be used at temps over 600°F (316°C) |
| Appearance | Red or black silicone in caulking tube |
| Specific Gravity | 1.06 |
| Injection Characteristics | 500 psi, flows well with minimum hydraulic pressure if injected with high pressure lubricator; may be poured or used with caulking gun |
| Cure | Flexible solid with moisture cure |
| Long Term Changes | None |
| Storage | 70°F or lower |

Packaging Information

| Item Number | Unit Size | Quantity |
|-------------|-----------|------------|
| CS170111 | Cartridge | 12 per box |

DO NOT USE ON OXYGEN SERVICE.
Special packaging sizing available upon request.

SOUTH COAST PRODUCTS

P.O. Box 450109 Houston, Texas 77245 www.socousa.com
Tel: (713) 225-0048 (800) 535-5823 custserv@socousa.com

Premium