



# Check Seal™ 20AB

## Dielectric Two-Component Sealant

**Check Seal™ 20AB** is a two-component, rubber type sealant developed for the electrical utility industry and commonly used for transformer leaks. It is available in both fast and slow cure formulas delivered in a two part, pre-measured kit for easy application. Both parts are mixed then applied with a high-pressure lubricator. Check Seal™ 20 can be used for sealing flange gaskets, valve stems, drain plugs and couplings. It can also be used in conjunction with clamps.

### Typical Characteristics

Applications	Transformer oils, fuels, hot oils, refrigerants, alcohols, chemicals and solvents CAUTION: Some of the additives in the steam and bfw can kill the cure.
<b>Note: For chemicals, refer to compatibility chart</b>	
Temperature Range	-300°F to 275°F
Limitations	Should not be used at temps over 275°F (135°C)
Appearance	Off-white resin paste with dark catalyst
Injection Characteristics	500 psi, flows well with high pressure applicator but can be poured directly into place
Cure	Semi-hard rubber that is removable; fast and slow cure rates available (temperature dependent)
Long Term Changes	None
Storage	70°F or lower

### Packaging Information

Item Number	Unit Size	Quantity
CS200811	12 oz. with syringe	16 per box
CS206411	1/2" gal kit, 6 lb	

**DO NOT USE ON OXYGEN SERVICE.**  
Special packaging sizing available upon request.

**SOUTH COAST PRODUCTS**

P.O. Box 450109 Houston, Texas 77245 www.socousa.com  
Tel: (713) 225-0048 (800) 535-5823 custserv@socousa.com

