



Check Seal™ 8AB

Two-Component Sealant

Check Seal™ 8AB is a two-component sealant that cures to an elastomeric plastic consistency for extreme shock resistance. It is recommended for cyclical or shock applications.

Typical Characteristics

| | |
|--|---|
| Applications | Transformer oil, SF6 gas, fuels, hot oil, water and steam CAUTION: Some of the additives in the steam and bfw can kill the cure. |
| Note: For chemicals, refer to compatibility chart | |
| Temperature Range | -300°F to 450°F |
| Limitations | Should not be used at temps over 450°F (232°C) |
| Appearance | White and blue pastes |
| Volume | 191 cu. in – 1 gal kit |
| Injection Characteristics | 500 psi, flows well with minimum hydraulic pressure |
| Cure | Hard elastomeric set, rate depends on temperature |
| Long Term Changes | None |
| Storage | 70°F or lower |

Packaging Information

| Item Number | Unit Size |
|-------------|-----------------|
| CS800111 | 1 gal kit, 9 lb |

DO NOT USE ON OXYGEN SERVICE.
Special packaging sizing available upon request.

SOUTH COAST PRODUCTS

P.O. Box 450109 Houston, Texas 77245 www.socousa.com
Tel: (713) 225-0048 (800) 535-5823 custserv@socousa.com

Premium