



# Check Seal™ 55 R

## Elastomeric Sealant

Check Seal™ 55 R is an elastomeric, nitrile rubber type sealant that cures to a hard rubber and works great on hot condensate or boiler feedwater leaks. It can be injected by a high-pressure sealant/lubricator gun.

### Typical Characteristics

Applications	Fuels, glycols, mild acids, aliphatic hydrocarbons, hot oils, kerosene, steam, bfw and liquors
<b>Note: For chemicals, refer to compatibility chart</b>	
Temperature Range	-300°F to 450°F
Limitations	Should not be used at temps over 450°F
Appearance	Black rubber stick
Injection Characteristics	Must be injected with high pressure sealant gun
Cure	Cures to hard rubber, makes a hard carbon seal at higher temperatures
Long Term Changes	None
Storage	70°F or lower

### Packaging Information

Item Number	Unit Size	Quantity
CS550111	5/8" x 3" plugs	100 minimum

**DO NOT USE ON OXYGEN SERVICE.**

*Special packaging sizing available upon request.*

# SOUTH COAST PRODUCTS

P.O. Box 450109 Houston, Texas 77245 [www.socousa.com](http://www.socousa.com)  
Tel: (713) 225-0048 (800) 535-5823 [custserv@socousa.com](mailto:custserv@socousa.com)

## Premium