



Check Seal™ 11RTV Silicone Sealant

Check Seal™ 11RTV is a one-component silicone sealant that cures to a pliable, low durometer solid. It is formulated for use with water and steam-based services.

Recommended Uses

Can be used as aerospace gasketing or for encapsulation of heating elements and other bonding/sealing of parts subjected to temperatures 500°F or below.

Typical Characteristics

Applications	Acids, glycols, hydrocarbons, refrigerants, water, steam, bfw and many solvents
Note: For chemicals, refer to compatibility chart	
Temperature Range	50°F to 500°F (10°C to 260°C)
Limitations	Should not be used at temps over 500°F (260°C)
Appearance	Black silicone in caulking tube
Specific Gravity	1.06
Injection Characteristics	500 psi, flows well with minimum hydraulic pressure if injected with high pressure lubricator; may be poured or used with caulking gun
Cure	Flexible solid with moisture cure
Long Term Changes	None
Storage	70°F or lower

Packaging Information

Item Number	Unit Size	Quantity
CS110111	Cartridge	12 per box
CS110611	5 Gal	

DO NOT USE ON OXYGEN SERVICE.
Special packaging sizing available upon request.

SOUTH COAST PRODUCTS

P.O. Box 450109 Houston, Texas 77245 www.socousa.com
Tel: (713) 225-0048 (800) 535-5823 custserv@socousa.com

Premium