



Check Seal™ 357P Non-Curing Sealant

Check Seal™ 357P is a non-curing sealant that contains a blend of non-asbestos fibers in synthetic oils. It works great on valve packing repairs and wire wrap fugitive emission repairs, and is specifically designed for high temperature hydrocarbon service up to 750°F. It is pumpable with a high pressure (10,000 psi) lubrication hand gun.

Typical Characteristics

Applications	Glycols, hydrocarbons, water, steam, bfw and many solvents. Good general purpose, high temperature valve sealant.
Note: For chemicals, refer to compatibility chart	
Temperature Range	40°F to 750°F (4°C to 399°C)
Appearance	Black, fibrous
Injection Characteristics	900 psi - Flows well at higher pressures
Cure	Non-curing
Storage	Keep in dry area

Packaging Information

Item Number	Unit Size	Quantity
CS082316JBX	300J-12 "J" stick 1-3/8" x 8-1/2"	16 per box
CS0823001PL	3/4" x 4" plugs	10 per pouch

DO NOT USE ON OXYGEN SERVICE.
Special packaging sizing available upon request.

SOUTH COAST PRODUCTS

P.O. Box 450109 Houston, Texas 77245 www.socousa.com
Tel: (713) 225-0048 (800) 535-5823 custserv@socousa.com

Premium