



Check Seal™ 42

Fast Curing Epoxy Putty

Check Seal™ 42 is a hand-mixable, fast curing, epoxy putty that can be ready for use in just one minute. One hour after mixing, Check Seal™ 42 can be drilled, sawed, sanded, filed, tapped, machined or painted. Packaged in a “no mess” 4 oz “tootsie-roll” application, the curing agent is encapsulated in the contrasting resin, eliminating drips and runs and requiring no tools. It provides fast repairs to many surfaces including metals, wood, glass, concrete, ceramics and numerous plastics. Approved for NSF 61 applications.

Typical Characteristics

Applications	Hydrocarbons, ketones, esters, gasoline, liquors, oils, bfw, alcohols, refrigerants and diluted acids
Note: For chemicals, refer to compatibility chart	
Temperature Range	40°F to 300°F (4°C to 148°C)
Limitations	Should not be used at temps over 300°F (148°C)
Appearance	Gray stick with encapsulated catalyst
Injection Characteristics	Hand applied adhesive, no injection
Cure	After 60 minutes, may be drilled, sanded, painted, etc. Cures to full strength in 24 hours
Long Term Changes	Long term UV ray exposure may break down material
Storage	Keep at room temperature

Packaging Information

Item Number	Unit Size	Quantity
CS420111	7" tubes	12 per box
CS420211	7" tubes	24 per box

DO NOT USE ON OXYGEN SERVICE.
Special packaging sizing available upon request.

SOUTH COAST PRODUCTS

P.O. Box 450109 Houston, Texas 77245 www.socousa.com
Tel: (713) 225-0048 (800) 535-5823 custserv@socousa.com

Premium