



Chemola™ Desco Black Wellhead Packing P-Seal Energizer

Chemola™ Desco Black Wellhead Packing is a broad range injectable packing material compounded with a blend of synthetic oils, non-fiberglass synthetic fibers, dry film lubricant and inert fillers.

Recommended Uses

Used as P-Seal energizing medium in wellhead installations and maintenance.

Typical Characteristics

Appearance	Black
NLGI	>6
Penetration (ASTM D217)	55-65
Base Oil	Synthetic
Base Oil Viscosity	200 cSt at 25°C
Base Oil Pour Point	-85°F (-65°C)
Solids Content	Synthetic fibers, fillers
Specific Gravity	1.4
Density (lb/gal)	11.6
Dropping Point (ASTM D566)	>500°F (260°C)
Flash Point	>625°F (326°C)
Temperature Range	-70°F to 250°F (-59°C to 122°C)

Packaging Information

Item Number	Unit Size	Quantity
0886010BX	3/4 x 4	10 per box
088616JBX	"J" stick 1-3/8" x 8-1/2"	16 per box

DO NOT USE ON OXYGEN SERVICE.
Special packaging sizing available upon request.

SOUTH COAST PRODUCTS

P.O. Box 450109 Houston, Texas 77245 www.socousa.com
Tel: (713) 225-0048 (800) 535-5823 custserv@socousa.com

Premium