



## Chemola™ Desco HS Pak Injectable Packing

**Chemola™ Desco HS Pak** is a synthetic lubricant and packing with a high resistance to hydrogen sulfide and hydrocarbons. It is pumpable with a high pressure (10,000 psi) lubrication hand gun.

### Recommended Uses

Resistant to carbon dioxide, molten sulfur, water, salt and aliphatic hydrocarbons

### Typical Characteristics

Appearance	Black, grainy
NLGI	6
Penetration (ASTM D217)	80-130
Base Oil	Synthetic esters
Base Oil Viscosity	30,000 cSt at 40°C
Base Oil Pour Point	10°F (-12°C)
Solids Content	Synthetic fibers, fillers
Specific Gravity	1.3
Density (lb/gal)	10.7
Dropping Point (ASTM D566)	>500°F (260°C)
Flash Point	>500°F (260°C)
Temperature Range	0°F to 400°F (-18°C to 204°C)

### Packaging Information

Item Number	Unit Size	Quantity
086372BBX	"B" stick 3/8" x 1-1/2"	72 per box
086316JBX	"J" stick 1-3/8" x 8-1/2"	16 per box
086312KBX	"K" stick 1-1/2" x 10-1/2"	12 per box
0863010QB	5 qt can, 10 lb can	

**DO NOT USE ON OXYGEN SERVICE.**  
*Special packaging sizing available upon request.*

# SOUTH COAST PRODUCTS

P.O. Box 450109 Houston, Texas 77245 [www.socousa.com](http://www.socousa.com)  
Tel: (713) 225-0048 (800) 535-5823 [custserv@socousa.com](mailto:custserv@socousa.com)

## Premium