



## Chemola™ Desco TFE Versi-Pak Injectable Packing Sealant

**Chemola™ Desco TFE Versi-Pak** is an injectable packing compound containing TFE-fluorocarbon particles blended into a synthetic binder. It is a highly versatile and durable self molding packing for use in stuffing boxes and for all types of valves, pumps and mechanical equipment. It can be either pre-formed manually or pumped into place with a high pressure (10,000 psi) grease gun. TFE Versi-Pak is chemically stable and resistant to most chemicals over a wide pH range.

### Recommended Uses

Chemola™ Desco TFE Versi-Pak is a permanent packing which can be supplemented and does not need to be replaced.

### Typical Characteristics

Appearance	White, grainy, sticky
NLGI	6
Penetration (ASTM D217)	80-90
Base Oil	Synthetic
Base Oil Viscosity	650 cSt at 100°C
Base Oil Pour Point	41°F (5°C)
Solids Content	PTFE
Specific Gravity	1.6
Density (lb/gal)	13.7
Flash Point	392°F (200°C)
Temperature Range	-20°F to 450°F (-29°C to 232°C)

### Packaging Information

Item Number	Unit Size	Quantity
081572BBX	"B" stick 3/8" x 1-1/2"	72 per box
081532CBX	"C" stick 7/16" x 2-1/8"	32 per box
081528DBX	"D" stick 1/2" x 2-1/4"	28 per box
081514GBX	"G" stick 5/8" x 3-1/2"	14 per box
081516JBX	"J" stick 1-3/8" x 8-1/2"	16 per box
081512KBX	"K" stick 1-1/2" x 10-1/2"	12 per box
0815005QB	10 lb	
0815012WP	10 lb pail	
0815025WP	25 lb pail	
0815040WP	40 lb pail	
0815120KG	120 lb keg	

**DO NOT USE ON OXYGEN SERVICE.**  
*Special packaging sizing available upon request.*

# SOUTH COAST PRODUCTS

P.O. Box 450109 Houston, Texas 77245 [www.socousa.com](http://www.socousa.com)  
Tel: (713) 225-0048 (800) 535-5823 [custserv@socousa.com](mailto:custserv@socousa.com)

## Premium