

Descos 960 is an economical body-fill grease designed to purge water and other contaminants from body cavity, to protect valve from the damage and corrosion that occurs during storage and other site conditions. Recent formulation enhancements have improved resistance and metal adherence to deliver reliable protection and resistance across a wider temperature range.

Recommended Uses

Excellent for lubricating valves, post-hydrotesting, prior to storage or shipping.

Typical Characteristics

Appearance	Black, smooth
NLGI	2
Penetration (ASTM D217)	265-295
Worked Penetration, 60x (ASTM D217)	265-295
Base Oil	Mineral oil 145
Base Oil Viscosity	cSt at 40°C
Base Oil Pour Point	-10°F (-23°C)
Thickener	Inorganic
Additives	Antioxidant/corrosion inhibitor package
Solids Content	Graphite
Specific Gravity	0.9
Density (lb/gal)	7.8
Dropping Point (ASTM D566)	>500°F (260°C)
Flash Point	>400°F (204°C)
Temperature Range	-18°F to 350°F (-28°C to 177°C)

Packaging Information

DESCO 960 is available in various package sizes and weights. When inquiring, please refer to DESCO 960 Part No. 0114

DO NOT USE ON OXYGEN SERVICE.
Special packaging sizing available upon request.

SOUTH COAST PRODUCTS

P.O. Box 450109 Houston, Texas 77245 www.socousa.com
Tel: (713) 225-0048 (800) 535-5823 custserv@socousa.com