



Chemola™ Desco Lithium Complex EP

Enhanced Lubrication Formula

Chemola™ Desco Lithium Complex EP is formulated as a wide-ranging multi-purpose grease with excellent extreme pressure resistance, shearability, shelf life, water resistance, and anti-corrosion properties, offering the additional protection to meet today's high performance requirements.

Recommended Uses

Roller bearings, ball bearings, journal bearings and extreme pressure sliding applications. Also excellent for general industrial use.

Typical Characteristics

Lithium Complex	
Appearance	Amber, smooth
NLGI	2
Penetration (ASTM D217)	265-295
Worked Penetration, 60x (ASTM D217)	265-295
Base Oil	Mineral oil
Base Oil Viscosity	143 cSt at 40°C
Base Oil Viscosity	11 cSt at 100°C
Base Oil Viscosity Index	40
Base Oil Pour Point	-10°F (-23°C)
Thickener	Lithium complex
Specific Gravity	0.9
Density (lb/gal)	7.5
Dropping Point (ASTM D566)	500°F (260°C)
Flash Point	455°F (235°C)
Temperature Range	0°F to 300°F (-18°C to 150°C)
Four-Ball EP Weld Point (ASTM D2596)	250 kgf
Timken OK	30 lbs

Packaging Information

Item Number	Unit Size	Quantity
0225010CR	14 oz cartridge	10 per case
0225035BM	35 lb pail	
0225120KG	120 lb keg	
0225400DR	400 lb drum	

DO NOT USE ON OXYGEN SERVICE.
Special packaging sizing available upon request.

SOUTH COAST PRODUCTS

P.O. Box 450109 Houston, Texas 77245 www.socousa.com
Tel: (713) 225-0048 (800) 535-5823 custserv@socousa.com

Premium