



Chemola™ Desco 625-PAK

Injectable Packing with PTFE and Aramid Fibers

Chemola™ Desco 625 Pak is our most popular blend of 100% synthetic base oils with synthetic fibers and fillers that provide a sure seal. The base fluids provide a very low coefficient of expansion (from -80° F to 500° F) while being oil resistant. The solid synthetic fibers and fillers provide a sure seal and are inert to most services.

Recommended Uses

Chemola™ Desco 625 Pak can be used in hydrocarbons, steam, water, sour gas and sour crude. It is pumpable with a high pressure (10,000 p.s.i.) lubrication hand gun.

Typical Characteristics

Appearance	Green, grainy
NLGI	>6
Penetration (ASTM D217)	30-60
Base Oil	Synthetic
Base Oil Viscosity	60,000 cSt at 25°C
Base Oil Pour Point	-40°F (-40°C)
Solids Content	Synthetic fibers, fillers
Specific Gravity	1.4
Density (lb/gal)	11.9
Dropping Point (ASTM D566)	>500°F (260°C)
Flash Point	>450°F (260°C)
Temperature Range	-80°F to 500°F (-62°C to 260°C)

Packaging Information

Item Number	Unit Size	Quantity
084272BBX	"B" stick 3/8" x 1-1/2"	72 per box
084216JBX	"J" stick 1-3/8" x 8-1/2"	16 per box
084214GBX	"G" stick 5/8" x 3-1/2"	14 per box
0842010BP	10 lb	
0842040WMS	40 lb	

***Ribbons and coils available upon request.**

DO NOT USE ON OXYGEN SERVICE.
Special packaging sizing available upon request.

SOUTH COAST PRODUCTS

P.O. Box 450109 Houston, Texas 77245 www.socousa.com
Tel: (713) 225-0048 (800) 535-5823 custserv@socousa.com

Premium