

Chemola[™] Desco 660 Hydrocarbon Service for McEvoy Type Valves

Chemola™ Desco 660 is a superior gate valve lubricant/sealant formulated with 100% synthetic oils and non-soap thickeners. It is very effective in gas service (except chlorine, bromine, fluorine, and oxygen) and highly resistant to washout. It has excellent metal adhesion, corrosion resistance, EP characteristics and is water resistant.

Recommended Uses

Chemola™ Desco 660 can be used in aliphatic hydrocarbons, alkalis, dilute acids, salt water, water, sour crude and sour gas.

Typical Characteristics

| Appearance | Dark green, smooth, tacky |
|--|-------------------------------|
| NLGI | 0 |
| Penetration (ASTM D217) | 355-385 |
| Worked Penetration, 60x (ASTM D217) | 355-385 |
| Base Oil | Synthetic ester |
| Base Oil Viscosity | 30,000 cSt at 40°C |
| Base Oil Pour Point | 10°F (-12°C) |
| Thickener | Inorganic |
| Additives | Antioxidant package |
| Specific Gravity | 1.3 |
| Density (lb/gal) | 11.1 |
| Dropping Point (ASTM D566) | >500°F (260°C) |
| Flash Point | >550°F (288°C) |
| Temperature Range | 0°F to 400°F (-18°C to 204°C) |
| Resistance to Water (FTM 5415) | Pass |
| Resistance to 50% Ethanol in Water (FTM5415) | Pass |
| Resistance to Synthetic Condensate (FTM 5415 mod) | Pass |
| Resistance to Mineral Spirits (FTM 5415 mod) | Pass |
| Resistance to 20% Hexane in Mineral Spirits (FTM 5415 mod) | Pass |
| Resistance to Diesel Fuel (FTM 5415 mod) | Pass |
| Resistance to Brine, 135°F (53°C) (ASTM D1748 mod) | Pass |

*FOR USE IN GATE VALVES.

DO NOT USE ON OXYGEN SERVICE.Special packaging sizing available upon request.

SOUTH COAST PRODUCTS

P.O. Box 450109 Houston, Texas 77245 www.socousa.com Tel: (713) 225-0048 (800) 535-5823 custserv@socousa.com





Chemola[™] **Desco 660**Hydrocarbon Service for McEvoy Type Valves

Packaging Information

| Item Number | Unit Size |
|-------------|-------------|
| 0826010QB | 10 lbcan |
| 0826025WMS | 25 lb pail |
| 0826040WMS | 40 lb pail |
| 0826120KG | 120 lb keg |
| 0826400DR | 400 lb drum |

*FOR USE IN GATE VALVES.

DO NOT USE ON OXYGEN SERVICE.Special packaging sizing available upon request.

SOUTH COAST PRODUCTS

P.O. Box 450109 Houston, Texas 77245 www.socousa.com Tel: (713) 225-0048 (800) 535-5823 custserv@socousa.com



