



Chemola™ Desco 960

Body Fill

Chemola™ Desco 960 is formulated for valves that contain body cavities. It is an economical body fill that will displace water and other containments. Chemola™ Desco 960 has high metal adhesion to lubricate and seal gates as they enter the body cavity.

Recommended Uses

Chemola™ Desco 960 is excellent for use in lubricating valves after hydrostatic testing for storage or shipping.

Typical Characteristics

Appearance	Gray, smooth
NLGI	2
Penetration (ASTM D217)	255-265
Worked Penetration, 60x (ASTM D217)	255-265
Base Oil	Mineral oil
Base Oil Viscosity	145 cSt at 40°C
Base Oil Pour Point	-10°F (-23°C)
Thickener	Inorganic
Additives	Antioxidant/corrosion inhibitor package
Solids Content	Graphite
Specific Gravity	0.9
Density (lb/gal)	7.8
Dropping Point (ASTM D566)	>500°F (260°C)
Flash Point	>400°F (204°C)
Temperature Range	-10°F to 350°F (-23°C to 177°C)

Packaging Information

Item Number	Unit Size	Quantity
0114010CR	14 oz cartridge	10 per carton
0114010CN	10 lb can	
0114020WMS	20 lb pail	
0114035WMS	35 lb pail	
0114120KG	120 lb keg	
0114400DR	400 lb drum	

DO NOT USE ON OXYGEN SERVICE.
Special packaging sizing available upon request.

SOUTH COAST PRODUCTS

P.O. Box 450109 Houston, Texas 77245 www.socousa.com
 Tel: (713) 225-0048 (800) 535-5823 custserv@socousa.com

Premium