

Chemola™ Desco Extreme-Pak

Extreme Temperature Injectable Packing

Chemola™ Desco Extreme-Pak is a pumpable packing and sealant specially formulated for water and steam service under high- and low-temperature conditions. It is pumpable using high-pressure (10,000 psi) lubrication hand gun even at sub-zero temperatures. Chemola™ Desco Extreme-Pak contains silicone oils with inert fillers and synthetic fibers.

Recommended Uses

Aqueous solutions, hydrocarbons (low temperature), steam and water

Typical Characteristics

Appearance	Blue
NLGI	>6
Penetration (ASTM D217)	50-65
Base Oil	Silicone oil
Base Oil Viscosity	40,000 cSt at 25°C
Base Oil Pour Point	-65°F (-54°C)
Solids Content	Synthetic fibers, fillers
Specific Gravity	1.5
Density (lb/gal)	12.3
Dropping Point (ASTM D566)	>500°F (260°C)
Flash Point	>620°F (326°C)
Temperature Range	-70°F to 600°F (-56°C to 315°C)

Packaging Information

Item Number	Unit Size	Quantity
085972BBX	"B" stick 3/8" x 1-1/2"	72 per box
085916JBX	"J" stick 1-3/8" x 8-1/2"	16 per box
085912KBX	"K" stick 1-1/2" x 10-1/2"	12 per box
0859040BM	40 lb metal pail	

DO NOT USE ON OXYGEN SERVICE.

Special packaging sizing available upon request.