



## Chemola™ Desco Green Wellhead Pak Packing Energizer

**Chemola™ Desco Green Wellhead Pak** is a proprietary packing formulation that has been developed primarily for the energizing of elastomer seals in crossover bushings in wellhead applications. It has also been used quite successfully as a packing energizer in blowout preventers. A blend of silicone oils and inert synthetic fibers allows for lubrication and the necessary bridging capabilities.

### Typical Characteristics

Appearance	Green
NLGI	>6
Penetration (ASTM D217)	10-30
Base Oil	Silicone oil
Base Oil Viscosity	60,000 cSt at 25°C
Base Oil Pour Point	-40°F (-40°C)
Solids Content	Synthetic fibers, fillers
Specific Gravity	1.3
Density (lb/gal)	10.5
Dropping Point (ASTM D566)	>500°F (260°C)
Flash Point	>500°F (260°C)
Temperature Range	-70°F to 250°F (-57°C to 121°C)

### Packaging Information

Item Number	Unit Size	Quantity
0836002BX	5/8" x 1" stick	35 per box
0836010BX	3/4" x 4" stick	10 per box
083616JBX	"J" stick 1-3/8" x 8-1/2"	16 per box

**DO NOT USE ON OXYGEN SERVICE.**  
*Special packaging sizing available upon request.*

# SOUTH COAST PRODUCTS

P.O. Box 450109 Houston, Texas 77245 [www.socousa.com](http://www.socousa.com)  
Tel: (713) 225-0048 (800) 535-5823 [custserv@socousa.com](mailto:custserv@socousa.com)

## Premium