

Chemola[™] ThredOn[®] Copperhead Premium Copper Compound

Chemola™ ThredOn® Copperhead is a premium drill collar and tool joint compound formulated to prevent downhole make-up even under high drilling torques. It contains copper flake and other time-proven solid lubricants and additives in a high quality grease base. It resists water washout and provides easier breakout without galling.

Special Features and Benefits

- Premium environmentally friendly drill pipe and drill collar compound
- Contains special rust and corrosion inhibitors plus extreme pressure additives
- ► High temperature stability, solid lubricants contine to protect to 1500°F
- Doubles as a premium anti-seize compound and high temperature lubricant

Typical Characteristics

Appearance	Copper, smooth	
NLGI	1	
Penetration (ASTM D217)	300-330	
Worked Penetration, 60x (ASTM D217)	300-330	
Base Grease	Lithium Complex	
Base Oil	Mineral oil	
Base Oil Viscosity	140 cSt at 40°C	
Base Oil Viscosity	10 cSt at 100°C	
Base Oil Pour Point	-10°F (-23°C)	
Solids Content	Copper, graphite, minerals	
Specific Gravity	1.2	
Density (lb/gal)	9.8	
Dropping Point (ASTM D566)	500°F (260°C)	
Flash Point	430°F (221°C)	
Temperature Range	0°F to 500°F (-18°C to 260°C)	
Four-Ball EP Weld Point (ASTM D2596)	620 kgf	
Friction Factor (API 7A1)	1.1 (can be torqued to 1.15)	
Brushable To	0°F (-18°C)	
Sulfur Content	<0.15%	

^{*}Contains no lead.

Special packaging sizing available upon request.

SOUTH COAST PRODUCTS

^{*}Available in Arctic Grade DO NOT USE ON OXYGEN SERVICE.

Chemola[™] ThredOn[™] Copperhead Premium Copper Compound

Item Number	Unit Size	Quantity
0304010BP	10 lb pail	
0304006BT	1/2 pint can	12 per case
0304012BT	1 pint can	12 per case
0304025BM	25 lb metal pail	
0304025BP	25 lb pail	
0304045BP	45 lb pail	
0304045BM	45 lb metal pail	

*Contains no lead.

*Available in Arctic Grade
DO NOT USE ON OXYGEN SERVICE.

Special packaging sizing available upon request.

SOUTH COAST PRODUCTS

Premium