



Chemola™ ThredOn® LDD

Zinc Base for Light Duty Drilling

Chemola™ ThredOn® LDD contains oxidation inhibitor to increase shelf life and special wetting agents help to coat even wet threads. It prevents galling and makes for easy breakouts in light duty drilling applications.

Recommended Uses

Light duty drilling

Typical Characteristics

Appearance	Grey to black, smooth
NLGI	1
Penetration (ASTM D217)	300-330
Worked Penetration, 60x (ASTM D217)	300-330
Base Grease	Lithium Complex
Base Oil	Mineral oil
Base Oil Viscosity	140 cSt at 40°C
Base Oil Viscosity	10 cSt at 100°C
Base Oil Pour Point	-10°F (-23°C)
Solids Content	Zinc
Specific Gravity	1.3
Density (lb/gal)	10.7
Dropping Point (ASTM D566)	500°F (260°C)
Flash Point	430°F (221°C)
Temperature Range	0°F to 500°F (-18°C to 260°C)
Brushable To	0°F (-18°C)
Sulfur Content	<0.3%

***Contains no lead.**

Do Not Use On Oxygen Lines

DO NOT USE ON OXYGEN SERVICE.

Special packaging sizing available upon request.

SOUTH COAST PRODUCTS

P.O. Box 450109 Houston, Texas 77245 www.socousa.com
Tel: (713) 225-0048 (800) 535-5823 custserv@socousa.com

Premium