



# Chemola™ ThredOn™ Texas Special

## Lead-Free Thread Compound for Tubing and Casing

**Chemola™ ThredOn™ Texas Special** is a lead free alternative to API Modified compound. Texas Special is formulated with an exclusive solids additive package to insure a positive seal and ease of break-out. Texas Special Thread Compound will prevent galling or damage to threads and is easy to apply to dry or wet threads.

### Recommended Uses

Texas Special adheres to the performance requirements of API 5A3 for use as a thread sealant and lubricant on line pipe including tubing and casing.

### Typical Characteristics

Appearance	Dark copper, smooth
NLGI	1
Penetration (ASTM D217)	300-330
Worked Penetration, 60x (ASTM D217)	300-330
Base Grease	Lithium Complex
Base Oil	Mineral oil
Base Oil Viscosity	140 cSt at 40°C
Base Oil Viscosity	10 cSt at 100°C
Base Oil Pour Point	-10°F (-23°C)
Solids Content	Copper, zinc
Specific Gravity	1.5
Density (lb/gal)	12.9
Dropping Point (ASTM D566)	500°F (260°C)
Flash Point	430°F (221°C)
Temperature Range	0°F to 500°F (-18°C to 260°C)
Friction Factor (API 7A1)	1.0
Brushable To	0°F (-18°C)
Sulfur Content	<0.3%

### Packaging Information

Item Number	Unit Size
0358035BM	35 lb metal pail
0358050BP	50 lb pail

**\*Contains no lead.**  
**DO NOT USE ON OXYGEN SERVICE.**  
*Special packaging sizing available upon request.*

# SOUTH COAST PRODUCTS

P.O. Box 450109 Houston, Texas 77245 [www.socousa.com](http://www.socousa.com)  
 Tel: (713) 225-0048 (800) 535-5823 [custserv@socousa.com](mailto:custserv@socousa.com)

## Premium