



Chemola™ Desco Blue Extreme

Premium Industrial Grease

Chemola™ Desco Blue Extreme is a premium industrial grease for use in applications where temperatures fluctuate and excellent water resistance is required.

Typical Characteristics

| | |
|-------------------------------------|-------------------------------|
| Appearance | Blue, smooth |
| NLGI | 1 |
| Penetration (ASTM D217) | 300-330 |
| Worked penetration, 60x (ASTM D217) | 300-330 |
| Base oil | Synthetic blend |
| Base oil viscosity | 36 cSt at 100°C |
| Base oil viscosity index | 140 |
| Base oil pour point | -19°F (-28°C) |
| Thickener | Inorganic |
| Specific gravity | 0.9 |
| Density (lb/gal) | 7.5 |
| Dropping point (ASTM D566) | >500°F (260°C) |
| Flash point | 400°F (200°C) |
| Temperature range | -10°F – 350°F (-23°C - 177°C) |

Characteristics

| Item Number | Unit Size |
|-------------|--------------------------|
| 0538010CR | 14 oz cartridge, 10/case |
| 0538120KG | 120 lb drum |
| 0538400DR | 400 lb drum |

DO NOT USE ON OXYGEN SERVICE.
Special packaging sizing available upon request.

SOUTH COAST PRODUCTS

P.O. Box 450109 Houston, Texas 77245 www.socousa.com
Tel: (713) 225-0048 (800) 535-5823 custserv@socousa.com

Premium