

ThredOn 301 EZE Break Drill Collar Safety Data Sheet

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Identification of the substance or mixture

Product Name: ThredOn 301 EZE Break Drill Collar
Product Use: Thread compound, lubricant
Manufacturer: South Coast Products
20 Southbelt Industrial Dr
Houston, TX 77047 USA
Emergency telephone number: +1 813 248 0585, 24 hours
Refer to code 0301

E-mail address for questions regarding this SDS: sharons@socousa.com

2. HAZARDS IDENTIFICATION

GHS Classification

Acute aquatic toxicity (Category 1)
Chronic aquatic toxicity (Category 1)

GHS label elements



Signal Word:

Warning

Hazard statements:

H410 – Very toxic to aquatic life with long lasting effects

Precautionary statements:

P273 – Avoid release to the environment

P391 – Collect spillage

P501 – Dispose of contents/container to an approved waste disposal plant

Other hazards: High pressure injection under skin is a medical emergency.

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical name | EC no. | CAS no. | Weight % |
|---------------|-----------|-----------|----------|
| Zinc | 231-175-3 | 7440-66-6 | 5-10 |
| Zinc oxide | 215-222-5 | 1314-13-2 | 5-10 |

ThredOn 301 EZE Break Drill Collar

Safety Data Sheet



4. FIRST AID MEASURES

- General:** If exposed or concerned, get medical attention or advice.
- Inhalation:** Move exposed person to fresh air. Get medical attention if symptoms occur. No symptoms expected.
- Ingestion:** Wash out mouth with water. Do not induce vomiting unless instructed to by medical personnel. Get medical attention if nausea or stomach pains occur.
- Skin contact:** Remove contaminated clothing and shoes. Wash skin with soap and water. Get medical attention if irritation symptoms occur. High pressure injection under skin is a medical emergency.
- Eye contact:** Check for and remove any contact lenses. Immediately flush eyes with running water for at least 5 minutes, keeping eyelids open. Get medical attention if redness or irritation persists.

5. FIRE-FIGHTING MEASURES

- Suitable media:** Use dry chemical, CO₂, water spray (fog) or foam.
- Not suitable:** Do not use water jet.
- Combustion products:** Carbon monoxide, carbon dioxide, products of incomplete hydrocarbon combustion, toxic fluoride compounds.
- Special protective equipment for fire-fighters:** Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus with a full face-piece operated in positive pressure mode.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions:** Wear appropriate personal protection equipment (see section 8).
- Environmental precautions:** Recover free product. Use suitable oil adsorbent and dispose of material in accordance with all regulations. Keep product out of sewers and watercourses, prevent soil penetration. Advise authorities if large amounts of product enters waterways or extensive land areas.

7. HANDLING AND STORAGE

- Handling:** Wear appropriate personal protection equipment (see section 8). Do not eat, drink or smoke when using. Wash thoroughly after handling. Follow good hygiene and housekeeping practices.
- Storage:** Store in cool dry area in original or equivalent container in accordance with all regulations. Do not expose to extreme heat or flame. Store below 65°C, away from strong oxidizers and acids.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- Engineering controls:** Use with adequate ventilation.
- Eye/face protection:** Safety glasses. Ensure eye bath is to hand.
- Hand protection:** Protective gloves if prolonged or repeated contact is unavoidable.

ThredOn 301 EZE Break Drill Collar

Safety Data Sheet



Skin protection: No additional protection required beyond normal industrial attire is required.

Respiratory protection: No special measures required.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and odor: Gray, grainy semi-solid, mild odor

pH: Not applicable, insoluble in water

Flash point: >200°C (Cleveland open cup)

Evaporation rate: No data

Upper flammability limit: Not applicable

Lower flammability limit: Not applicable

Vapor pressure: No data

Vapor density: No data

Relative density: 1.3

Solubility: Insoluble in water, soluble in alcohols and petroleum distillates

Viscosity: Cone penetration 330-350 (ASTM D-217)

10. STABILITY AND REACTIVITY

Chemical stability: Stable

Conditions to avoid: Extreme heat

Incompatible materials: Strong oxidizers

Hazardous decomposition products: Harmful or flammable vapors, toxic fluoride compounds

11. TOXICOLOGICAL INFORMATION

Potential acute health effects

Acute toxicity:

- Ingestion:** Harmful if swallowed
- Skin contact:** No known effect
- Inhalation:** Harmful if inhaled, but not considered significant route of entry

Irritation: May cause mild redness and discomfort on contact with eyes

Corrosivity: Not corrosive

Potential chronic health effects

Sensitization: Not a sensitizer

Repeated dose toxicity: Repeated exposure may cause drying of skin from loss of skin oils

Carcinogenicity: No ingredients listed as carcinogens

Mutagenicity: Not mutagenic

Reproductive toxicity: Not a reproductive toxin

STOT repeated exposure: No effects known

12. ECOLOGICAL INFORMATION

ThredOn 301 EZE Break Drill Collar

Safety Data Sheet



Ecotoxicity: Toxic to aquatic life with long lasting effects

| Chemical name | Toxicity to algae | Toxicity to fish | Toxicity to daphnia |
|---------------|------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|-----------------------------------------------|
| Zinc | Pseudokirchneriella subcapitata, 96h, EC50: 0.11-0.271 mg/L | Pimephales premelas 96h, LC50: 2.16-3.05 mg/L Cyprinus carpio, 96h, LC50: 7.8 mg/L | Daphnia magna, 48h, EC50: 0.139-0.908 mg/L |
| Zinc oxide | Pseudokirchneriella subcapitata, 72h, EC50: 0.042 mg/L Pseudokirchneriella subcapitata, 96h, NOEC: 0.017 mg/L | Lepomis machochirus 96h, LC50: 320 ppm | Daphnia magna, 48h, EC50: 98 µg/L |

Persistence/degradability: No information available

Bioaccumulative potential: High, BCF = 60960

Mobility: No information available

Other adverse effects: No information available

13. DISPOSAL CONSIDERATIONS

Waste disposal: Generation of waste should be avoided or minimized where possible. Empty containers may contain residue. Dispose of as hazardous waste via licensed waste disposal operator. Follow all applicable regulations.

14. TRANSPORT INFORMATION

Transport information according to USDOT: Not restricted

Transport information according to ADR, RID, ADN, IMDG, ICAO, IATA

UN number: UN3077

Proper shipping name: Environmentally hazardous substance, solid, n.o.s. (zinc)

Hazard class: Class 9

Packing group: PGIII

Marine Pollutant: No

15. REGULATORY INFORMATION

OSHA Hazards: None

SARA 311/312 Hazard classes: None

SARA 313: Ingredients subject to reporting requirements: zinc, CAS-No. 7440-66-6

Massachusetts Right To Know Components: zinc, CAS-No. 7440-66-6

Pennsylvania Right To Know Components: zinc, CAS-No. 7440-66-6; zinc oxide, CAS-No. 1314-13-2

New Jersey Right To Know Components: zinc, CAS-No. 7440-66-6; zinc oxide, CAS-No. 1314-13-2

California Prop 65 Components: This product does not contain any chemicals known to the State of California to cause cancer, birth defects or any other reproductive harm.


16. OTHER INFORMATION

ThredOn 301 EZE Break Drill Collar Safety Data Sheet

Hazardous Material Information System (USA):

| | |
|---------------------|---|
| HEALTH | 0 |
| FIRE | 1 |
| REACTIVITY | 0 |
| PERSONAL PROTECTION | B |

National Fire Protection Association (USA):



Revision information: Original GHS compliant issue 1 Aug 2014. Rev 1: reviewed with no changes. Rev 2: reviewed with no changes.

END OF SAFETY DATA SHEET