



Chemola™ Desco PLV 55X Sealant

Pipeline Valve Sealant - Premium

Chemola™ Desco PLV 55X is a premium synthetic sealant for hard to seal valves. It is formulated for excellent resistance to washout from hydrocarbons, and contains chemically inert PTFE for ultimate sealing capability. Higher PTFE grades are available.

Recommended Uses

Chemola™ Desco PLV 55X is designed for use in ball and gate valves in gas transmission and distribution systems.

Designed for use by qualified technicians only
Can cause ball check valve fittings to fail

Typical Characteristics

Appearance	Black, tacky, grainy
NLGI	4
Penetration (ASTM D217)	175-205
Worked Penetration, 60x (ASTM D217)	175-205
Base Oil	Synthetic and natural esters
Base Oil Viscosity	1000 cSt at 40°C
Base Oil Pour Point	10°F (-12°C)
Thickener	Inorganic
Additives	Corrosion inhibitor
Solids Content	PTFE
Specific Gravity	1.0
Density (lb/gal)	8.3
Dropping Point (ASTM D566)	>500°F (260°C)
Flash Point	>500°F (260°C)
Temperature Range	-20°F to 350°F (-29°C to -177°C)

Packaging Information

Item Number	Unit Size
0426010QB	10 lb / 5 qt can
0426040BM	40 lb metal pail
0426120KG	120 lb keg
0426400DR	400 lb drum

DO NOT USE ON OXYGEN SERVICE.
Special packaging sizing available upon request.

SOUTH COAST PRODUCTS

P.O. Box 450109 Houston, Texas 77245 www.socousa.com
Tel: (713) 225-0048 (800) 535-5823 custserv@socousa.com

Premium