

FROM THE MAKERS OF CHEMOLA™ DESCO
VALVE LUBRICANTS AND SELALANTS.

SOCO

PRO-CLEAN

SOCO Pro-Clean is a formulated multi-ingredient, semi-fluid combination of penetrants and lubricants designed to dissolve and cut residual gums, lacquer deposits, inert solids, and corrosion deposits that make valves non-functioning and hard to operate.

Although not all valves are recoverable with Pro-Clean, a popular maintenance suggestion is the periodic use of Pro-Clean. By utilizing this suggestion, many operators have found that valves remain operable through years of usage under severe conditions.

TYPICAL CHARACTERISTICS

| | |
|-------------------------|-----------------------|
| Appearance | Black, smooth |
| NLGI | 1 |
| Penetration (ASTM D217) | 320-350 |
| Specific gravity | 0.9 |
| Density (lb/gal) | 7.8 |
| Flash point | 154°-158°F (68°-70°C) |
| Temperature range | Up to 150°F (65°C) |

20 Southbelt Industrial Dr
Houston, TX 77047
713-225-0048
socousa.com



Recommended Use

For neglected valves. Helps to free frozen and non-sealing valves so that routine maintenance can be commenced. When the valve is again operational SOCO Pro-Clean must be purged from the valve by injecting the recommended SOCO Pro Series Lubricant/Sealant for the particular service of the valve.

Available in these sizes:

10 lb pail

40 lb pail

Other sizes available on request

PREMIUM

SOCO

SOUTH COAST PRODUCTS