

FROM THE MAKERS OF CHEMOLA™ DESCO
VALVE LUBRICANTS AND SEALANTS.

SOCO

PRO-LUBE ARCTIC

SOCO Pro-Lube Arctic is a synthetic lubricant formulated to reduce operating torque in pipeline valves in extremely low temperatures.

TYPICAL CHARACTERISTICS

Appearance	Blue, smooth
NLGI	2
Penetration (ASTM D217)	265-295
Worked penetration, 60x (ASTM D217)	265-295
Base oil	Synthetic
Base oil viscosity	17 cSt at 100°C
Base oil pour point	-65°F (-54°C)
Thickener	Inorganic
Specific gravity	0.9
Density (lb/gal)	7.5
Dropping point (ASTM D566)	>500°F (260°C)
Flash point	370°F (188°C)
Temperature range	-75°F – 400°F (-59°C - 204°C)



Recommended Use

Pro-Lube Arctic is recommended for Ball, Gate and Plug valves found on gas and liquid transmission and gathering lines, as well as valve on gas distribution systems in arctic environments.

Available in these sizes:

Cartridges

10 lb pail

40 lb pail

J Sticks

Other sizes available on request

PREMIUM

20 Southbelt Industrial Dr
Houston, TX 77047
713-225-0048
socousa.com

SOCO
SOUTH COAST PRODUCTS