

FROM THE MAKERS OF CHEMOLA™ DESCO  
VALVE LUBRICANTS AND SEALANTS.

# SOCO

## PRO-LUBE MAX

SOCO Pro-Lube Max is formulated for superior hydrocarbon resistance for use upon commissioning valves. It contains molybdenum disulfide for added temperature and extreme pressure properties. Pro-Lube Max is our most widely used pipeline valve lubricant.

### TYPICAL CHARACTERISTICS

Appearance	Black, tacky, smooth
NLGI	4
Penetration (ASTM D217)	185-215
Worked penetration, 60x (ASTM D217)	185-215
Base oil	Ester blend
Base oil viscosity	1500 cSt at 40°C
Base oil pour point	-20°F (-29°C)
Thickener	Inorganic
Specific gravity	1.0
Density (lb/gal)	8.6
Dropping point (ASTM D566)	>500°F (260°C)
Flash point	>500°F (260°C)
Temperature range	-40°F – 350°F (-40°C - 177°C)



### Recommended Use

Pro-Lube Max is recommended for Ball, Gate and Plug valves found on gas and liquid transmission and gathering lines, as well as valves on gas distribution systems.

Available in these sizes:

- Cartridges
- 10 lb pail
- 40 lb pail
- J Sticks
- Other sizes available on request

**PREMIUM**

20 Southbelt Industrial Dr  
Houston, TX 77047  
713-225-0048  
socousa.com

**SOCO**  
SOUTH COAST PRODUCTS