

FROM THE MAKERS OF CHEMOLA™ DESCO
VALVE LUBRICANTS AND SEALANTS.

SOCO

PRO-LUBE SEAL

SOCO Pro-Lube Seal is a premium synthetic lubricant and sealant for pipeline valves over a wide temperature range. It is formulated for excellent resistance to washout from hydrocarbons and contains chemically inert fillers for ultimate sealing capability.

TYPICAL CHARACTERISTICS

Appearance	Dark Orange, tacky, grainy
NLGI	3
Penetration (ASTM D217)	210-240
Worked penetration, 60x (ASTM D217)	210-240
Base Oil	Synthetic and natural esters
Base oil viscosity	1000 cSt at 40°C
Base oil pour point	10°F (-12°C)
Thickener	Inorganic
Additives	Corrosion inhibitor
Solids content	Inert fibers and fillers
Specific gravity	1.0
Density (lb/gal)	8.3
Dropping point (ASTM D566)	>500°F (260°C)
Flash point	>500°F (260°C)
Temperature range	-40°F - 350°F (-40°C - 177°C)

20 Southbelt Industrial Dr
Houston, TX 77047
713-225-0048
socousa.com



Recommended Use

Pro-Lube Seal is recommended for Ball, Gate and Plug valves found on gas and liquid transmission and gathering lines, as well as valve on gas distribution systems.

Available in these sizes:
Cartridges
10 lb pail
40 lb pail
J Sticks
Other sizes available on request

PREMIUM

SOCO
SOUTH COAST PRODUCTS