

FROM THE MAKERS OF CHEMOLA™ DESCO
VALVE LUBRICANTS AND SEALANTS.

SOCO

PRO-LUBE SEAL

SOCO Pro-Lube Seal is a premium synthetic lubricant and sealant for pipeline valves over a wide temperature range. It is formulated for excellent resistance to washout from hydrocarbons and contains chemically inert fillers for ultimate sealing capability.

TYPICAL CHARACTERISTICS

Appearance	Dark Orange, tacky, smooth
NLGI	3
Penetration (ASTM D217)	210-240
Worked penetration, 60x (ASTM D217)	210-240
Base Oil	Synthetic and natural esters
Base oil viscosity	1000 cSt at 40°C
Base oil pour point	10°F (-12°C)
Thickener	Inorganic
Additives	Corrosion inhibitor
Solids content	Inert fibers and fillers
Specific gravity	1.0
Density (lb/gal)	8.3
Dropping point (ASTM D566)	>500°F (260°C)
Flash point	>500°F (260°C)
Temperature range	-40°F – 350°F (-40°C - 177°C)



Recommended Use

Pro-Lube Seal is recommended for Ball, Gate and Plug valves found on gas and liquid transmission and gathering lines, as well as valve on gas distribution systems.

0543B10CR	114oz CARTRIDGES10/BX
0543B10QB	5QT CAN 10# NET
0543B16JBX	“J” STICKS 16/BX
0543B35BM	35# METAL PAIL

Other packaging sizes
available upon request

PREMIUM

20 Southbelt Industrial Dr
Houston, TX 77047
713-225-0048
socousa.com

SOCO
SOUTH COAST PRODUCTS