

FROM THE MAKERS OF CHEMOLA™ DESCO
VALVE LUBRICANTS AND SELALANTS.



SOCO Pro-Lube is a superior lubricant formulated to protect valves, especially during installation and startup. Pro-Lube is our standard lubricant for use in pipeline valves, and is resistant to a wide range of hydrocarbons including natural gas, crude, and oil products.

TYPICAL CHARACTERISTICS

Appearance	Light orange, tacky, smooth
NLGI	2
Penetration (ASTM D217)	220-250
Worked penetration, 60x (ASTM D217)	220-250
Base oil	Ester
Base oil viscosity	1000 cSt at 40°C
Base oil pour point	5°F (-15°C)
Thickener	Inorganic
Specific gravity	1.0
Density (lb/gal)	8.3
Dropping point (ASTM D566)	>500°F (260°C)
Flash point	>500°F (260°C)
Temperature range	-20°F – 350°F (-29°C - 177°C)



Recommended Use

Pro-Lube is recommended for Ball, Gate, and Plug valves found on gas and liquid transmission and gathering lines, as well as valves on gas distribution systems.

Available in these sizes:

Cartridges

10 lb pail

40 lb pail

J Sticks

Other sizes available on request

PREMIUM

20 Southbelt Industrial Dr
Houston, TX 77047
713-225-0048
socousa.com

