

FROM THE MAKERS OF CHEMOLA™ DESCO
VALVE LUBRICANTS AND SEALANTS.

SOCO

PRO-PAK EXTRA

SOCO Pro-Pak Extra is an injectable packing compound with synthetic base oils, fibers, and fillers. The base fluids provide for minimal expansion and contraction over Pro-Pak Extra's temperature range (-80 °F to 500 °F) while being oil resistant. The solid synthetic fibers and fillers provide a sure seal and are inert to most services.

TYPICAL CHARACTERISTICS

Appearance	Green, grainy
NLGI	>6
Penetration (ASTM D217)	30-60
Base Oil	Synthetic
Base oil viscosity	60,000 cSt at 25°C
Base oil pour point	-40°F (-40°C)
Solids content	Inert fibers, fillers
Specific gravity	1.4
Density (lb/gal)	11.9
Flash point	>450°F (232°C)
Temperature range	-80°F – 500°F (-62°C - 260°C)



Recommended Use

Pro-Pak Extra is recommended for Ball, Gate and Plug valves found on gas and liquid transmission and gathering lines, as well as valve on gas distribution systems.

Available in these sizes:
Cartridges
10 lb pail
40 lb pail
J Sticks
Other sizes available on request

PREMIUM

20 Southbelt Industrial Dr
Houston, TX 77047
713-225-0048
socousa.com

SOCO
SOUTH COAST PRODUCTS