

FROM THE MAKERS OF CHEMOLA™ DESCO  
VALVE LUBRICANTS AND SEALANTS.

# SOCO

## PRO-PAK HT

SOCO Pro-Pak HT is a non-curing, pumpable packing that contains a blend of fibers and fillers in synthetic fluids. Pro-Pak HT is specifically designed for high-temperature hydrocarbon service. It is pumpable with a high-pressure (10,000 p.s.i) lubrication hand gun.

### TYPICAL CHARACTERISTICS

Appearance	Black
NLGI	>6
Penetration (ASTM D217)	50-60
Base oil	Synthetic and natural esters
Base oil viscosity	500 cSt at 40°C
Base oil pour point	-4°F (-16°C)
Solids content	Synthetic fibers, fillers
Specific gravity	1.4
Density (lb/gal)	11.8
Flash point	>550°F (288°C)
Temperature range	-40°F – 750°F (-40°C - 400°C)

20 Southbelt Industrial Dr  
Houston, TX 77047  
713-225-0048  
socousa.com



### Recommended Use

Pro-Pak HT is recommended for Ball, Gate and Plug valves found on gas and liquid transmission and gathering lines, as well as valve on gas distribution systems

Available in these sizes:

- 10 lb pail
- 40 lb pail
- J Sticks
- Other sizes available on request

**PREMIUM**

**SOCO**  
SOUTH COAST PRODUCTS