

FROM THE MAKERS OF CHEMOLA™ DESCO
VALVE LUBRICANTS AND SEALANTS.

SOCO

PRO-PAK

SOCO Pro-Pak is an injectable packing compound containing inert fibers and particles blended into a synthetic binder. It is a highly versatile and durable self-molding packing for use in stuffing boxes and for all types of valves, pumps, and mechanical equipment. It can be either pre-formed manually or pumped into place with a high-pressure (10,000 p.s.i.) grease gun. Pro-Pak is chemically stable and resistant to most chemicals over a wide pH range.

TYPICAL CHARACTERISTICS

Appearance	White, sticky, grainy
NLGI	6
Penetration (ASTM D217)	80-90
Base Oil	Synthetic
Base oil viscosity	650 cSt at 100°C
Base oil pour point	41°F (5°C)
Solids content	Inert fibers and fillers
Specific gravity	1.6
Density (lb/gal)	13.7
Flash point	392°F (200°C)
Temperature range	-20°F – 350°F (-29°C - 177°C)



Recommended Use

Pro-Pak is recommended for Ball, Gate, and Plug valves found on gas and liquid transmission and gathering lines, as well as valves on gas distribution systems. It is a permanent packing that can be supplemented and does not need to be replaced.

Available in these sizes:

- 10 lb pail
- 40 lb pail
- J Sticks

Other sizes available on request

PREMIUM

20 Southbelt Industrial Dr
Houston, TX 77047
713-225-0048
socousa.com

SOCO
SOUTH COAST PRODUCTS