

FROM THE MAKERS OF CHEMOLA™ DESCO
VALVE LUBRICANTS AND SELALANTS.

SOCO

PRO-SEAL

SOCO Pro-Seal is a premium synthetic sealant for hard-to-seal valves. It is formulated for excellent resistance to washout from hydrocarbons and contains chemically inert polymer fibers for ultimate sealing capability. Higher polymer grades are available.

TYPICAL CHARACTERISTICS

Appearance	Dark Blue, tacky, grainy
NLGI	3
Penetration (ASTM D217)	210-240
Worked penetration, 60x (ASTM D217)	210-240
Base Oil	Synthetic and natural esters
Base oil viscosity	1000 cSt at 40°C
Base oil pour point	10°F (-12°C)
Thickener	Inorganic
Additives	Corrosion inhibitor
Solids content	Inert fibers and fillers
Specific gravity	1.0
Density (lb/gal)	8.3
Dropping point (ASTM D566)	>500°F (260°C)
Flash point	>500°F (260°C)
Temperature range	-20°F – 350°F (-29°C - 177°C)

20 Southbelt Industrial Dr
Houston, TX 77047
713-225-0048
socousa.com



Recommended Use

Pro-Seal is recommended for Ball, Gate, and Plug valves found on gas and liquid transmission and gathering lines, as well as valves on gas distribution systems.

Available in these sizes:

Cartridges

10 lb pail

40 lb pail

J Sticks

Other sizes available on request

PREMIUM

SOCO
SOUTH COAST PRODUCTS