

FROM THE MAKERS OF CHEMOLA™ DESCO
VALVE LUBRICANTS AND SEALANTS.

SOCO

PRO-BLOCK

SOCO Pro-Block is a semi-synthetic sealant especially formulated to seal leaking gate and ball valves with downstream seats. It has high metal adhesion to lubricate and seal gates as they enter the body cavity



TYPICAL CHARACTERISTICS

Appearance	Black, tacky, grainy
NLGI	3
Penetration	(ASTM D217) 220-240
Worked penetration	0x (ASTM D217) 220-240
Base oil	Mineral oil/synthetic blend
Base oil viscosity	143 cSt at 100°C
Base oil viscosity	11 cSt at 40°C
Base oil viscosity index	40
Base oil pour point	-10°F (-23°C)
Solids content PTFE	PTFE
Additives	EP, antioxidant and corrosion inhibitors
Specific gravity	1.0
Density (lb/gal)	8-8.5
Dropping point (ASTM D566)	>500°F (260°C)
Flash point	>400°F (200°C)
Temperature range	Te-10°F – 350°F (-23°C - 177°C)

This product is only available for use by certified companies.

Available in these sizes:
1 gallon
5 gallon
Other sizes available on request

20 Southbelt Industrial Dr
Houston, TX 77047
713-225-0048
socousa.com

PREMIUM

SOCO

SOUTH COAST PRODUCTS